


Tubular Cable Lugs: DIN 46235

- Electrolytic high conductivity copper
- Electro tinned plated



Product Ref.	Conductor Size mm²	Stud Hole	Dimensions mm								
			E	I	B	W	E	O	C1	C2	L1
CD 6-5	6	M 5	3,8	10		8,5	5,3	5,5	6,5	7,5	24
CD 6-6	6	M 6				8,5	6,4		7,5	8	
CD 6-8	6	M 8				13	8,4		10	10	
CD 10-5	10	M 5	4,5	10		9	5,3	6	7	8,5	27
CD 10-6	10	M 6				9	6,4		7,5	8,5	
CD 10-8	10	M 8				13	8,4		10	10	
CD 16-6	16	M 6	5,5	20		13	6,4	8,5	7,5	8	36
CD 16-8	16	M 8				13	8,4		10	10	
CD 16-10	16	M 10				17	10,5		12	12	
CD 16-12	16	M 12				18	13		13	13	
CD 25-6	25	M 6	7	20		14	6,4	10	7,5	8	38
CD 25-8	25	M 8				16	8,4		10	10	
CD 25-10	25	M 10				17	10,5		12	12	
CD 25-12	25	M 12				19	13		13	13	
CD 35-6	35	M 6	8,2	20		17	6,4	12,5	7,5	8	42
CD 35-8	35	M 8				17	8,4		10	10	
CD 35-10	35	M 10				19	10,5		12	12	
CD 35-12	35	M 12				21	13		13	13	
CD 35-14	35	M 14				21	15		14,5	14,5	
CD 50-8	50	M 8	10	28		20	8,4	14,5	10	10	52
CD 50-10	50	M 10				22	10,5		12	12	
CD 50-12	50	M 12				24	13		13	13	
CD 50-14	50	M 14				24	15		14,5	14,5	
CD 50-16	50	M 16				28	17		16	16	
CD 70-8	70	M 8	11,5	28		24	8,4	16,5	10	10	55
CD 70-10	70	M 10				24	10,5		12	12	
CD 70-12	70	M 12				24	13		13	13	
CD 70-14	70	M 14				24	15		14,5	14,5	
CD 70-16	70	M 16				30	17		16	16	
CD 95-8	95	M 8	13,5	35		28	8,4	19	12	12	65
CD 95-10	95	M 10				28	10,5		12	12	
CD 95-12	95	M 12				28	13		13	13	
CD 95-14	95	M 14				28	15		14,5	14,5	
CD 95-16	95	M 16				32	17		16	16	
CD 120-10	120	M 10	15,5	35		32	10,5	21	15	16	70
CD 120-12	120	M 12				32	13		16	17	
CD 120-14	120	M 14				32	15		18	18	
CD 120-16	120	M 16				32	17		19	20	
CD 120-20	120	M 20				38	21		21	22	